



PRODUCTS SUPPORT PRESS CENTER ABOUT SAMSUNG

Canada | English

PRODUCTS

Computers & Related Products

Printer and Multifunction

[Colour Laser Printer](#)

[Laser Printer](#)

Multi Function Products

[Photo Printer](#)

[Supplies and Accessories](#)

[Archived Printer](#)

[Monitor](#)

[Optical Disk Drive](#)

[Hard Disk Drive](#)



[SITE FRANÇAIS](#) [PRODUCT REGISTRATION](#) [SEARCH](#)

GO

[Home](#) > [Products](#) > [Computers & Related Products](#) > [Printer](#) > [Multi Function Products](#)



SCX-5530FN

Network Ready, Laser Printer, Fax, Copier and Color Scanner

The Samsung SCX-5530FN Network Ready Office Laser Printer, Fax, Copier and Color Scanner A powerful print, fax, copy and scan solution that features print and copy speeds up to 30 ppm. USB 2.0 and IEEE-1284 parallel ports and 10/100 networking standard. Enhanced scanning resolution up to 4800 dpi. TWAIN compatible. Comes standard with Samsung's exclusive USB Direct port for computer-free scanning and printing.

[FAQs](#)

[Sales Location](#)

[Service Location](#)

[+ Image View](#)

Select Model [GO](#)

[Features](#) | [Specifications](#)

Specifications

	Print/ Fax/ Copy/ Scan / Imprimer/ télécopier/ copieScan	Yes/Yes/Yes/Yes
	Weight / Poids	18.5 kg
	Dimensions (WxDxH) / Dimensions (LxPxH)	466 x 435.4 x 458 mm
	LCD / ACL	2 line x 16 characters
General / Généralités	Interface / Interface	USB 2.0 (High Speed), IEEE 1284 (Parellel), Ethernet 10/100 base Tx -Windows 98/Me/NT4.0/2000/XP - Various Linux OS (via USB interface only) including Red Hat 8~9, Fedora Core 1~3, Mandrake 9.2~10.1, and SuSE 8.2~9.2 -Mac 10.3, 10.4
	OS Compatibility / Compatibilité système d'exploitation	
	Speed / Vitesse	30 ppm
	Resolution / Résolution	Up to 1200 dpi Effective Output
Print Specifications / Caractéristiques de l'imprimante	Print language / Langage d'impression	PCL6, PS3
	Duplex / Duplex	Standard
	Toner Save / Économie d'encre	Yes
	Transmission Speed / Vitesse de transmission	33.6 Kbps,3 sec/page
	Communication System / Système de communication	Public Switched Telephone Network (PSTN) or behind PABX
Fax Specifications / Caractéristiques du télécopieur	Fax Compatibility, ECM / Support ECM	ITU-T Group 3
	Coding Method / Méthode de codage	MH / MR / MMR (ECM Mode) / JBIG / JPEG
	Resolution / Résolution	Up to 400 x 400 dpi
	Memory Capacity / Capacité de la mémoire	6 MB (Approx. 480 pages at ITU-T #1 Chart)
	Speed / Vitesse	30 ppm

Copy Specifications / Caractéristiques du copieur	Resolution (Scan, Print) / Résolution (Numérisation, impression)	Up to 600 x 600 dpi
	Zoom Range / Étendue du zoom	25~400% (platen), 25~100% (ADF)
	Multi-copies / Copies multiples	1~99 pages
Scanning Specifications / Caractéristiques de la numérisation	Resolution (Optical) / Résolution (optique)	600 x 1200 dpi
	Speed / Vitesse	Max. 4,800 x 4,800 dpi
	Scan Method / Méthode de numérisation	Color CCD
Paper Handling / Gestion des documents	Paper Input (Capa./Type) / Sortie papier (capacité/Type)	250-sheet Cassette Tray, 50- sheet MP Tray
	Output Capacity / Capacité de sortie	150-sheet Face Down, 1- sheet Face Up
	Toner Parts No. / Encre – No. Pièce	Standard Toner(4K) : SCX- D5530A High Yield Toner (8K) : SCX-D5530B
Consumables / Consommables	Toner Yield (@5% Coverage) / Quantité encre @ 5% couverture	Standard : 4,000 pages at ISO 19752 5% Coverage High Yield : 8,000 pages at ISO 19752 5% Coverage (Ships with 4,000 pages Standard Toner Cartridge)

▶ The information on this page meets my needs.

[Agree](#) [Disagree](#)

[+ Submit](#) |

PRIVACY | LEGAL
© 1995 -2007 SAMSUNG. All rights reserved.