

Tbits PS2 w/o Palmrest - KBS225T5



No DataSheet Available

[Click Here For Keyboard
Layout](#)

SOLIDUS
PERIPHERALS

Specification Data

Function and Operation:

- All keys are non-latching in nature
- Pseudo N-key rollover in nature
- 16 - character buffer (FIFO)
- 104/105 key layouts

Electrical Specification:

- Maximum Rating: +5.0 VDC \pm 10%, 200 mA maximum
- Contact Resistance: 500 Ohm maximum
- Insulation Resistance: DC100V 50M Ohm minimum
- Bounce: 10mS maximum

Mechanical Specifications:

- Total Travel: 4.0 \pm 0.5mm
- Pull Force: above 1.5 kg
- Dimensions: 480mm x 167mm
- Cable content: 26AWG.Single Wire x 4,
24AWG.Single Wire x 1
- Cable Length: 2 M (straight)

EMI/Safety and Reliability:

- EMI/Safety: FCC Class B, CE approval, UL, CSA and TUV (available on request)
- ESD Immunity: 0 KV to 8 KV minimum without any data loss (software); 8KV to 15KV minimum, may cause malfunctions but will not destroy any internal components (firmware)
- Operating Life: 10,000,000 times

Packaging:

- Each in single box
- 10 pcs per carton / 1.86 cuft